



Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 8844
F: 08 9277 4068
bondall@bondall.com
www.bondall.com

bondcrete

AM0004

Revised Oct 2001

Description

Bondall BondCrete is a very versatile sealing and bonding agent, used widely in the building and renovating industries. Some of BondCrete's many uses includes:
Toppings & repairs; rendering & plastering; tile fixing & grouting; sealing, binding & dustproofing; carpentry joinery & general craftwork; and decorative finishes.

FEATURES AND BENEFITS

- BondCrete the proven performer has evolved since 1951 into the most versatile bonding and sealing agent available.
- BondCrete contains an exclusive resin additive ensuring maximum bonding strength.
- BondCrete is so strong there is seldom any need to hack, chip or acid etch the surface before bonding.
- BondCrete is a concentrated high solid product, which in most cases provides a high dilution ratio, ensuring the customer gets value for money.

SURFACE PREPARATION


- Before applying BondCrete ensure that surface is free of dirt, dust, oil, grease and loose or flaking materials.
- Do not use BondCrete in wet or damp areas unless it is mixed and used in conjunction with cement. For waterproofing applications for wet areas, please refer to Bondall Hydrocrete, Bondall Silasec, Bondall Aquatite, Bondall Pondtite, Bondall Terratite and other Bondall waterproofing products.
- Do not use BondCrete in temperatures below 10 ° C.
- BondCrete is not recommended for bonding of plastic and rubber.

APPLICATION

- * **CARPENTRY, JOINERY & GENERAL CRAFT WORK:**
Apply direct from container to one surface only. Press surfaces together and lightly clamp. BondCrete sets in approx 30 minutes. Max strength is attained in 12 hours
- * **PRIMING AND SEALING PRIOR TO PAINTING:**
One sealing coat of diluted BondCrete (BondCrete1: water 4) will provide an excellent sealer or key when applied to new or old cement rendered walls, plaster etc. before using water borne decorative paints (see paint manufactures instructions). Allow 24 hours to dry. Do not attempt to apply oil-based paints over BondCrete.
- * **DUST PROOFING AND/OR RETARDING OIL PENETRATING OF INTERIOR CONCRETE FLOORS:**
To a clean floor apply a sealing coat of diluted BondCrete (BondCrete 1: water 6) by brush, roller or spray. Leave to dry for approximately 12 hours. Apply another sealing coat with a dilution of BondCrete (BondCrete 1: water 4), allow to dry. Please Note: do not seal floor with BondCrete if you intend to use an oil-based paving paint or similar floor coating system. For exterior use, apply Bondall Paving & Concrete Sealer.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

APPLICATION

* TOPPINGS RENDER OR PATCHING:

Apply sealer coat of BondCrete (BondCrete 1: water 4) allow to dry. Apply bondcoat of BondCrete (BondCrete 4: water 1) and while still wet or tacky carry out topping or patching. Use BondCrete admixture (BondCrete 1: water 10) in the topping/patching mixture in place of normal water.

* PLASTERING SETTINGS ONTO CONCRETE CEILINGS, WALLS ETC:

Apply one sealing coat of diluted BondCrete (BondCrete 1: water 4) allow to dry. Apply one bondcoat of diluted BondCrete (BondCrete 1: water 1) to the surface and while this coat is still tacky, plaster with hardwall plaster mixed to required consistency with BondCrete admix (BondCrete 1: water 4) in place of normal water.

* TILING:

Apply sealer coat of diluted BondCrete (BondCrete 1: water 4) to surface and allow to dry. Apply bondcoat of diluted BondCrete (BondCrete 1: water 1) to sealed surface and while still wet or tacky lay

bedding. Beddings up to 6mm - 1 part cement: 2 part fine sand

Beddings over 6mm - 1 part cement: 3 part fine sand

Mixed to a workable consistency with BondCrete admix (BondCrete 1:water 4) in place of normal water.

Screed bed-ting to required level and bed the tiles immediately.

As BondCrete has a multitude of other uses, the above are some of the more common uses for Bondcrete.

COVERAGE

Estimates below will provide a useful guide:

BondCrete undiluted = 3.5 square metres per litre

BondCrete Diluted:

BondCrete 4 parts: water 1 part = 8 square metres per litre

BondCrete 1 part: water 1 part = 17.5 square metres per litre

BondCrete 1 part: water 4 parts = 35 square metres per litre

BondCrete as an admix: BondCrete 1 part water 10 parts is an ideal admix ratio for cement toppings, concrete, plasters etc. For estimating purposes 2 litres of BondCrete diluted with 20 litres of water is normally sufficient for mixing each 40 kg bag of cement.

THINNING

BondCrete may be diluted with water when doing the following:

A sealing coat: (BondCrete 1: water 4)

A bondcoat: (BondCrete 1: water 1)

Bondall BondCrete as an admixture to sand and cement: (BondCrete 1: water 10)



Wholly Australian Owned & Manufactured

the solution **is** bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

GLOSS LEVEL

Not applicable.

DRYING TIME

Drying times vary pending on how it is being used and temperatures.

If applied neat: BondCrete sets in 30 minutes but attains maximum strength in 24 hours.

As a thumb rule allow application to dry for at least 24 hours before applying second coat.

CLEAN UP

DO NOT POUR CONTENTS OR WASHING DOWN DRAINS OR SINKS.

Clean equipment and spills with clean running water.

COLOUR

White liquid but dries clear.

SIZES

250mL, 500mL, 1L, 2L, 4L, 10L, 20L & 200L

PRECAUTION/FIRST AID

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation – use a suitable respirator if spray application is employed.

If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give water to drink and do not induce vomiting.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844 See Web Site: www.bondall.com.

For customer within the area of Indonesia, please contact our distributor PT. Bondall Kumala Jaya on (021) 2259 5588 or see website: www.indobondall.co.id



Wholly Australian Owned & Manufactured
the solution is bondall

